T/PUMP®

LOCALIZED THERAPY SYSTEM

Ease patient pain and discomfort



SAFE AND EFFECTIVE LOCALIZED WARMING AND COOLING THERAPY

The T/Pump® system provides safe and effective localized warming and cooling therapy with precise temperature control. Simple and versatile, T/Pump® is effective for chronic pain relief and patient comfort in orthopedic conditions, skin trauma and a number of other applications to meet the needs of an ever-changing patient population. The large, translucent reservoir and large buttons make operation simple.



The T/Pump stand provides ease of transporting to patient rooms and offers storage for pads and accessories. An IV pole mount plate is also available as a space saving solution.



Multiple temperature settings and treatment cycles allow for therapy that is customized to patient needs. Large buttons and LED indicators make operation simple and intuitive.



Extra wide leakproof cap includes a tethered strap to prevent cap loss. Simply fill with tap water for warming or tap water and ice for cooling.

- Conveniently operates with tap water without the need for sterile or distilled water.
- Three-layer safety system helps ensure safe operation.
- T/Flash technology provides a slight temperature change, providing patients with an "always there" feeling that the product is working.
- Ergonomic design with curved handle makes transport easy.
- Audible and visible alarms alert caregivers to low water or internal issues.
- Large translucent reservoir has a large capacity and allows users to determine water levels at a glance.





Standard Features

- 8.5' power cord
- · Hospital grade plug
- 93 oz (2750 mL) reservoir
- Large fill port (1-7/8" diameter)
- · Wet or dry storage

Optional Accessories

- TPS2 temperature therapy stand with storage basket and cord hooks
- TPIV bracket to clamp to IV pole to hold T/Pump

Opt. Test Accessories

- TPT9 flow meter
- Test probe assembly

Connector Options

- Clik-Tite Connectors are leakproof and multiple pads can be connected to one unit for multiple therapy sites
- 600 Series Mul-T-Pad water-circulating pads offer quick disconnect colder style connectors for increased adaptability with TP700C models

T/Pump® Specifications

Model Number	TP700, TP700C*
Height	11.5" (29 cm)
Width	8" (20 cm)
Depth	8" (20 cm)
Weight	Full (filled to heating water line) 9.3 lbs (4.2 kg) Empty - 6.7 lbs (3 kg)
Temp Range	10°C-42°C (50°F-107°F) Accuracy - ±2°F (1°C)
Fluid System	9 gph flow rate min

Electronics

Volts	8.120 VAC, 3.1 amps, 60 Hz, 20µA typical leakage current
Safety	UL approved to UL60601-1 and ASTM F2196

Warranty

1 Year	Medicare reimbursement HCPC E0217

Optional Mul·T·Pads

Lightweight, single patient use with Clik-Tite connectors

8002-062-012	Pliable polymer/nonwoven fabric on one side	13" x 18" (33 x 46 cm)		
8002-062-022	Pliable polymer/nonwoven fabric on one side	15" x 22" (38 x 56 cm)		
8002-062-026	Pliable polymer/nonwoven fabric on one side	18" x 26" (46 x 66 cm)		
Reusable				
8002-062-222	Heavy duty pliable polymer	15" x 22" (38 x 56 cm)		
600 series, single patient use with colder style connectors				
8002-062-612	Polymer/nonwoven fabric on both sides	13" x 18" (33 x 46 cm)		
8002-062-622	Polymer/nonwoven fabric on both sides	15" x 22" (38 x 56 cm)		
8002-062-626	Polymer/nonwoven fabric on both sides	18" x 26" (46 x 66 cm)		

Everis reserves the right to change specifications without notice.

*TP700 have Clik-Tite Connectors. TP700C have Colder Style Connectors.

Everis or its other corporate affiliated entities own, use or have applied for the following trademarks or service marks: Mult-T-Pad, T/Pump®, Everis. All other trademarks are trademarks of their respective owners or holder.



T/PUMP®

LOCALIZED THERAPY SYSTEM

Visit <u>www.everismedical.com</u> for more product information.



